



BRITE AUTO HIGH PRESSURE FOAMING DETERGENT

Brite Auto High Pressure Foaming Detergent is designed for high pressure wands used in self serve applications.

FEATURES & BENEFITS

- High foam
- Pleasant berry scent for customer appeal
- **Economical**

APPLICATION

Product Use Pressure Wand **Recommended Application**

1:1,000 to 1:3,000

Dilution ratios may need to be adjusted depending on cleaning conditions present.

NOTE: See reverse side for MSDS information and General Cautions for Use

VISIT OUR WEBSITE: WWW.VTLVEHICLECARE.COM

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Identity (As Used on Label and List): Brite Auto High Pressure Foaming Detergent

(EXT510)

Product Class: Water-based Cleaner

Emergency Telephone Number: 800-535-5053 (INFOTRAC)

Telephone Number for Information: 763-509-7937

Manufacturer's Name and Address:

Ver-tech Labs 6801 Bleck Drive Rockford MN 55373

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components (Specific Chemical Identity):

Chemical Common Name(s)

SECTION III - HAZARDS IDENTIFICATION

Emergency Overview

Appearance and Odor: Light Blue liquid, mild aroma.

Primary Hazards: Irritation

Potential Health Hazards

Skin Absorption: X Ingestion: X Route(s) of Entry: Inhalation: X

Eye: May cause Irritation on contact. Skin: May cause irritation on contact. Ingestion: Harmful if swallowed. Inhalation: No hazardous vapors.

Signs and Symptoms of Exposure: Eye Contact: Possible burning, tearing and redness. Skin Contact: Possible redness, swelling and irritation. Symptoms may be

delayed.

Carcinogenicity: NTP? No IARC Monographs? No

OSHA Regulated? No

Target Organ (s): Eyes, skin and mucous membranes.

Medical Conditions Generally Aggravated by Exposure: N. Av.

Health Hazards, Chronic: N. Av

SECTION IV - FIRST AID MEASURES

Emergency and First Aid Procedures:

For Eye Contact: Immediately flush eyes with sanitary eye wash solution or running water for at least 15 minutes. Obtain medical attention. If Swallowed: Do not induce vomiting Drink two glasses of water, call a physician. Never give anything by mouth to a unconscious person. For Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse.

Sources Used: Raw material data, general toxicology from the trade for

similar products

SECTION V - FIRE FIGHTING MEASURES

Flammability: No Autoignition Temperature: N. Ap.

Flash Point (method used): None Flammable Limits: N. Ap. LEL

UEL Extinguishing Media: N. Ap.

Water? Foam? Water Fog? Alcohol Foam? CO₂? Dry Chemical?

Vaporizing Liquid? Other? Special Fire Fighting Procedures: N. Ap. Unusual Fire and Explosion Hazards: TDG Flammability Classification: Non-flammable

Sensitivity to Mechanical Impact: None Sensitivity to Static Discharge: None

SECTION VI - ACCIDENTAL RELEASE MEASURES

Steps to be taken in Case Material is Released or Spilled:

Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area

SECTION VII - HANDLING AND STORAGE

Precautions to be taken in Handling and Storing:

Normal care in handling and storage.

Other Precautions: Keep out of reach of children. Keep from freezing.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Protection (Specify Types): Not required

Ventilation: Local Exhaust: Not required Special: Not required

Mechanical (General): As required to keep vapor levels below

TLV & PEL, listed in Section XI. Other: Not required

Protective Gloves: Natural rubber or synthetic.

Eye Protection: Approved safety goggles or shield. **Footwear:** Rubber footwear.

Other Protective Clothing or Equipment: Not required

Work/Hygienic Practices: Do not contaminate food or beverages with cleaning

chemicals

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 212°F (100°C)

Specific Gravity (H20) = 1: 1.01 % Volatile: 60 - 100 Vapor Density (Air = 1): N. Av. Odor Threshold: N. Av. Evaporation Rate (Butyl Acetate = 1): N. Av. Oil/Water Distribution Solubility in Water: Complete Coefficient: N. Av.

Vapor Pressure (MM HG):

Melting Point: N. Ap.

SECTION X - STABILITY AND REACTIVITY

Stability: Unstable:

Conditions to Avoid: N. Ap.

Incompatibility (materials to avoid): N. Av. Hazardous Decomposition or By-products: N. Av.

Will not occur: X Hazardous Polymerization: May occur:

Conditions to Avoid: N. Ap

SECTION XI - TOXICOLOGICAL INFORMATION

OSHA PEL **ACGIH TLV** LC50

Teratogen, Mutagen, Reproductive Toxin Status: No

Toxicologically Synergistic Products: N. Av.

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicological Information: N. Av.

Chemical Fate Information: N. Av SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of spilled material in accordance with local, state and federal regulations. Waste from normal cleaning procedures may be sewered, depending on the materials and/or contaminates being cleaned as well as state, federal and local sewer commission

regulations.

RCRA Hazard Class: N. Ap.

SECTION XIV - TRANSPORT INFORMATION

Shipping Classification: Compound Cleaning liquid UN Number:

Packing Group: SECTION XV - PREPARATION DATA

Prepared By: Health and Safety Department

Telephone Number: 763-509-7937

Date: 8-14-2008

SECTION XVI - REGULATORY INFORMATION

US Federal Regulations

TSCA Status: All ingredients listed. CERCLA Reportable Quality: N. Av.

SARA Title III

Section 302 Extremely Hazardous Chemicals: None

Section 311/312 Hazard Category: None Section 313 Toxic Chemic als: None

SECTION XVII - OTHER INFORMATION

None

N. Ap. - Not Applicable; N.Av. - Not Available

NFPA SYSTEM

0 A. Fire Hazard _0_ A. Reactivity Hazard 1 A. Health Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.