

MATERIAL SAFETY DATA SHEET

(COMPLIES WITH 29CFR 1910.1200)

SECTION I - CHEMICAL PRODUCT & COMPANY IDENTIFICATION	
Identity (As Used on Label and List): Evolution Plus (EXT148) Product Class: Drying Agent Emergency Telephone Number: 800-535-5053 (INFOTRAC) Telephone Number for Information: 763-509-7937 Manufacturer's Name and Address: Ver-tech Labs 6801 Bleck Drive Rockford, MN 55373	
SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS	
Hazardous Components (Specific Chemical Identity):	
Chemical	Common Name(s)
A	2-butoxy ethanol CAS #111-76-2
B	Mineral Seal Oil CAS #64742-46-7
SECTION III - HAZARDS IDENTIFICATION	
Emergency Overview	
Appearance and Odor: Amber liquid, solvent odor. Primary Hazards: Irritant	
Potential Health Hazards	
Route(s) of Entry: Skin Absorption: X Ingestion: X Inhalation: X Eye: May cause Irritation Skin: May cause Irritation Ingestion: May be harmful if swallowed. Inhalation: Overexposure to 2-Butoxy ethanol (butyl) / Mineral Seal Oil vapors may cause central nervous system effects including drowsiness, headaches, nausea and dizziness. Signs and Symptoms of Exposure: Irritation on direct contact. Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No Target Organ(s): Liver, kidneys, lymphoid system, skin, blood, eyes and respiratory system. Medical Conditions Generally Aggravated by Exposure: N. Av. Health Hazards, Chronic: Overexposure to 2-Butoxy ethanol (butyl) / Mineral Seal Oil may cause damage to one or more of the target organs listed above.	
SECTION IV - FIRST AID MEASURES	
Emergency and First Aid Procedures: If Swallowed: Do not induce vomiting. Drink water in large amounts and call a physician immediately. Never give anything by mouth to an unconscious person. Eye Contact: Flush eyes with running water for at least 15 minutes. If irritation persists, obtain medical attention. Skin Contact: Flush thoroughly with cool water. Remove and wash contaminated clothing before reuse. Sources Used: Raw material data, general toxicology from the trade for similar products.	
SECTION V - FIRE FIGHTING MEASURES	
Flammability: N. Av. Autoignition Temperature: N. Av. Flash Point (method used): None Flammable Limits: N. Av. LEL UEL Extinguishing Media: N. Av. Water? Foam? Water Fog? Alcohol Foam? CO2? Dry Chemical? Vaporizing Liquid? Other? Special Fire Fighting Procedures: N. Av. Unusual Fire and Explosion Hazards: N. Av. TDG Flammability Classification: Non-flammable Sensitivity to Mechanical Impact: None Sensitivity to Static Discharge: None	
SECTION VI - ACCIDENTAL RELEASE MEASURES	
Steps to be taken in Case Material is Released or Spilled: Dike and contain spill with inert material (sand, earth, etc). Collect spill with mop, absorbent material (example: floor-dri) or vacuum. Thoroughly rinse affected area with water.	
SECTION VII - HANDLING AND STORAGE	
Precautions to be taken in Handling and Storing: Normal care in handling and storage. Other Precautions: Keep out of reach of children. Keep from freezing.	
SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION	
Respiratory Protection (Specify Types): Not required Ventilation: Local Exhaust: Not required Special: Not required Mechanical (General): Ventilate to keep vapor levels below PEL and TLV, listed in Section XI. Other: Not required Protective Gloves: Natural rubber or synthetic. Eye Protection: Approved safety goggles or glasses. Footwear: Chemical resistant Other Protective Clothing or Equipment: Not required Work/Hygienic Practices: Do not contaminate food or beverages with cleaning chemicals.	

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: Approximately 212°F	pH: 7 -10				
Specific Gravity (H20) = 1: .9 -1.					
Vapor Density (Air = 1): > N. Av.	Odor Threshold: N. Av.				
Evaporation Rate (Butyl Acetate = 1): N. Av.	Oil/Water Distribution				
Solubility in Water: Dispersible	Coefficient: N. Av.				
Vapor Pressure (MM HG): N. Av.					
Melting Point: N. Av.					
SECTION X - STABILITY AND REACTIVITY					
Stability: Unstable: Stable: X					
Conditions to Avoid: N. Av.					
Incompatibility (materials to avoid): N. Av.					
Hazardous Decomposition or By-products: N. Av.					
Hazardous Polymerization: May occur: Will not occur: X					
Conditions to Avoid: N. Av.					
SECTION XI - TOXICOLOGICAL INFORMATION					
Chemical	OSHA PEL	ACGIH TLV	Recom.	LD50	LC50
A	25 ppm (skin)	25 ppm (skin)	25 ppm	1.48 g/kg (rat, oral)	N. Av.
B	5mg/m3.	N. Av.	N. Av.	5000 mg/kg (rat,oral)	N. Av.
Teratogen, Mutagen, Reproductive Toxin Status: No known relevance to humans.		Toxicologically Synergistic Products: N. Av.			
SECTION XII - ECOLOGICAL INFORMATION					
Ecotoxicological Information: N. Av. Chemical Fate Information: N. Av.					
SECTION XIII - DISPOSAL CONSIDERATIONS					
Waste Disposal Method: Dispose of spilled material in accordance with local, state and federal regulations. Waste from normal cleaning procedures may be sewerred, depending on the materials and/or contaminants being cleaned as well as state, federal and local sewer commission regulations. RCRA Hazard Class:					
SECTION XIV - TRANSPORT INFORMATION					
Shipping Classification: Cleaning Compound, n.o.s. UN Number: N. Av. Packing Group: N. Av.					
SECTION XV - PREPARATION DATA					
Prepared By: Health and Safety Department Telephone Number: 763-509-7937 Date: 5-28-2010					
SECTION XVI - REGULATORY INFORMATION					
US Federal Regulations TSCA Status: All ingredients listed. CERCLA Reportable Quality: N. Av. SARA Title III Section 302 Extremely Hazardous Chemicals: None Section 311/312 Hazard Category: Immediate health, chronic health. Section 313 Toxic Chemicals: 2-butoxy ethanol (glycol ether),					
SECTION XVII - OTHER INFORMATION					
None N. Av. - Not Applicable; N.Av. - Not Available					

NFPA SYSTEM

2 A. Health Hazard 0 A. Fire Hazard 0 A. Reactivity Hazard

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE, HOWEVER NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. MINUTEMAN INTERNATIONAL, INC. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.