



SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Manufacturer: Ver-tech Labs 6801 Bleck Drive Rockford, MN 55373 1-877-866-9742	Product Name: VAULT Drying Agent Product Code: VT-8020 Recommended Use: Drying agent Revision Date: 8/17/2021
--	--

Chemical Emergency: Infotrac: 1-800-535-5053

SECTION 2: HAZARDS IDENTIFICATION

GHS Hazard Classification

Flammable Liquid	Category 3
Acute Toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 1
Serious Eye Damage/Eye Irritation	Category 1
Aspiration Hazard	Category 1

Signal Word

DANGER!



Hazard Statements

Flammable liquid and vapor
 Harmful if swallowed
 Causes severe skin burns and eye damage
 Causes serious eye damage
 May be fatal if swallowed and enters airways

Precautionary Statements - Prevention

Keep away from heat/sparks/open flames/hot surfaces – No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/light/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection
 Wash thoroughly after handling
 Do not eat, drink or smoke when using this product
 Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

IF ON SKIN (or hair): Remove all contaminated clothing. Rinse skin with water/shower
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
 IF ON SKIN (or hair): Remove all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Precautionary Statements - Storage

Store in a well ventilated place. Keep cool
 Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

SECTION 3: INFORMATION ON HAZARDOUS INGREDIENTS

Product is a mixture according to 29 CFR 1910.1200.

Hazardous Components

Hazardous Ingredients	Cas #	Weight %
Distillates (petroleum), hydrotreated middle	64742-46-7	30 - 50%
Quaternary ammonium compounds	61789-77-3	15 - 30%
Tallow alkylamine ethoxylate	61791-26-2	5 - 15%
2-butoxyethanol	111-76-2	5 - 15%

Specific chemical identity and/or exact percentage of components has been withheld in accordance with a trade secret claim according to Appendix E 29 CFR 1910.1200.

SECTION 4: FIRST-AID MEASURES**First Aid Measures**

- General Advice:** Keep out of reach of children. Use with care.
- Eye Contact:** Immediately flush with cool running water for at least 15 minutes while holding eyelids apart. Do not rub affected area. Remove contact lenses if applicable.
- Skin Contact:** Wash off immediately with soap and water while removing all contaminated clothes and shoes.
- Ingestion:** If swallowed, call immediately for emergency medical assistance. DO NOT induce vomiting. Rinse mouth with water and drink 1-2 glasses of water. Never give anything by mouth to an unconscious person.
- Inhalation:** Remove to fresh air.

Most Important Symptoms and Effects

- Symptoms:** Severe burns to eyes, skin, and respiratory tract.

Indication of any immediate medical attention and special treatment needed

- Note to Physician:** Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES**Flammable Properties**

- Flammability:** Considered to be a fire hazard.
- Explosive Prop:** No information available.

Extinguishing Media

- Suitable:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable:** Do not use water jet as an extinguisher, as this will spread the fire.

Specific Hazards Arising from Chemical

- Hazards:** The product causes burns of eyes, skin and mucous membranes. Thermal decomposition may lead to release of irritating and toxic vapors. In the event of fire and/or explosion do not breathe fumes.

Protective equipment and precautions for fire-fighters

- Fire-Fight Method:** In the event of a fire, fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate personnel to safe areas. Isolate hazard area and deny entry. Stay upwind of spill/leak. Use personal protective equipment. Avoid contact with skin, eyes or clothing.

Environ. Precautions: Prevent release to the environment if possible. Dike large spills to prevent material from entering streams or sewer systems.

Clean-Up Method: Soak-up with inert absorbent material and place into appropriate container for disposal. Clean contaminated area thoroughly with water. Prevent product from entering drains.

SECTION 7: HANDLING AND STORAGE

- Handling:** Use personal protective equipment when needed. Avoid contact with skin, eyes, and clothing. Wash hands before eating, drinking, or smoking. Remove contaminated clothes and wash before reuse. Use in a ventilated area.
- Storage:** Store in closed containers in cool, dry, well-ventilated area. Avoid overheating or freezing. Keep in properly labeled containers and out of reach of children.
- Incomp. Materials:** Strong acids and bases. Oxidizing agents.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION**Exposure Guidelines**

Hazardous Chemical	OSHA PEL	ACGIH TLV
Distillates (petroleum), hydrotreated middle	No information available	No information available
Quaternary ammonium compounds	No information available	No information available
Tallow alkylamine ethoxylate	No information available	No information available
2-butoxyethanol	50 ppm	20 ppm

Appropriate Engineering Controls

- Eng. Controls:** Ensure adequate ventilation, especially in confined areas.

Personal Protection Equipment (PPE)

- Eyes:** Recommend safety goggles or shield.
- Respiratory:** Not usually necessary where ventilation is sufficient to maintain vapors under the TLV limit.
- Skin:** Avoid skin contact. Recommend chemical resistant gloves.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical State: Liquid	Freezing Point: Not determined
Appearance: Amber Liquid	Boiling Point: Not determined
Color: Amber	Evaporation Rate: Not determined
Odor: Solvent-like	Vapor Pressure: Not determined
Odor Threshold: No information available	Vapor Density: Not determined
pH: Neutral	Relative Density: Not determined
Flash Point: 95° F, closed cup	Flammability: Not determined
Water Solubility: Not determined	Explosive Limits: Not determined
Viscosity: Not determined	Part. Coefficient: Not determined
Specific Gravity: 0.860 - 0.870	Auto-ignition Temp: Not determined
Melting Point: Not determined	Decomp. Temp: Not determined

SECTION 10: STABILITY AND REACTIVITY

- Stability:** Stable under ordinary conditions of use and storage.
- Haz. Decomposition:** Thermal decomposition can lead to release of irritating and toxic gases and vapors.
- Haz. Polymerization:** No information available.
- Incompatibilities:** Strong acids and bases, strong oxidizing agents.
- Conditions to Avoid:** Heat, flames, sparks and incompatibles.

SECTION 11: TOXICOLOGY INFORMATION**Component Information**

Hazardous Chemical	LD50 Oral	LD50 Dermal
Distillates (petroleum), hydrotreated middle	No information available	No information available
Quaternary ammonium compounds	No information available	No information available
Tallow alkylamine ethoxylate	No information available	No information available
2-butoxyethanol	1,300 mg/kg (rat)	> 2,000 mg/kg (rat)

Potential Health Effects**Exposure Routes:** Eye Contact, Dermal Contact, Ingestion, Inhalation**Acute Toxicity:****Eyes:** Causes eye irritation with tearing, redness, and impaired vision.**Skin:** Causes skin irritation, redness, and itching. May cause chemical burns.**Ingestion:** Harmful if swallowed. Corrosive to mucous membranes, esophagus and stomach.**Inhalation:** Respiratory irritant.**Chronic Effects:** Avoid repeated exposure. May aggravate pre-existing medical conditions including eye, skin and respiratory disorders.**Carcinogenicity:** No data available.**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity**

Hazardous Chemical	Toxicity to Fish	Toxicity to Invertebrates
Distillates (petroleum), hydrotreated middle	No information available	No information available
Quaternary ammonium compounds	No information available	No information available
Tallow alkylamine ethoxylate	No information available	No information available
2-butoxyethanol	1,474 mg/l (96 h: Oncorhynchus mykiss)	1,550 mg/l (48 h: water flea)

Environmental Toxicity**Biodegradation:** No information available.**Persistence:** No information available.**Bioaccumulation:** No information available.**Mobility:** No information available.**SECTION 13: DISPOSAL CONSIDERATIONS****Waste Disposal:** Recover or recycle if possible. Disposal should be in compliance with applicable federal, state, and local regulations. Do not dispose of in the environment, in sewage, and/or in drains.**Container:** Drain contaminated container thoroughly. Do not reuse container.**SECTION 14: TRANSPORT INFORMATION***Transport in accordance with all federal, state, and local regulations.***DOT:** Not regulated as a dangerous good.**Special Provisions:** 173.150 Exceptions for Class 3 (flammable and combustible liquids). (b) Limited quantities (3) For flammable liquids in Packing Group III and combustible liquids, inner packagings not over 5.0 (1.3 gallons) net capacity, packed in strong outer packaging. 173.150 (b)(3).**SECTION 15: REGULATORY INFORMATION****US Federal Regulations****TSCA Status:** All components of this product are listed or exempt from listing on TSCA inventory.**CERCLA Reportable Quantity:** Not Applicable**Section 311/312 Hazard Category**

Acute Health Hazard:	61789-77-3	Quat Ammonium Compound	15 - 30%
	68155-39-5	Alkylamine ethoxylate	5 - 15%
	111-76-2	2-butoxyethanol	5 - 15%
Chronic Health Hazard:	No		
Fire Hazard:	61789-77-3	Quat Ammonium Compound	15 - 30%
	111-76-2	2-butoxyethanol	5 - 15%
Sudden Release of Pressure:	No		
Reactive Hazard:	No		
Section 313 Toxic Chemicals	111-76-2	2-butoxyethanol	5 - 15%

SECTION 16: OTHER INFORMATION

Prepared by: Health and Safety Department

Contact Number: 1-877-866-9742

Issue Date: 8/17/2021

Revision Date: 8/17/2021

Revision Note: New Product

Version: I

Disclaimer: The information provided in this Safety Data Sheet has been obtained from sources believed to be reliable. This information is offered for your information, consideration, and investigation. Ver-tech Labs cannot anticipate all conditions under which this information and its product may be used. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. It is the user's responsibility to assume liability for loss, injury, damage or expense due to improper use.

End of Safety Data Sheet